

**STANDARD HARNESS: DOUBLE LEG LANYARD WITH SCAFFOLDING HOOKS**  
HARN01220

**ONE SIZE FITS ALL**  
**STANDARDS:**  
SANS 50254 | EN 254 + SANS 50255 | EN 255  
SANS 50261 | EN 261 + EN 262

**FEATURES:**  
• Adjustable leg & chest straps  
• Shock absorbing lanyard

**MATERIALS:**  
Harness webbing: 45mm UV-resistant polyester webbing with a minimum breaking load of 2,5 tonnes

Lanyard webbing: 45mm UV-resistant polyester webbing with a minimum breaking load of 2,5 tonnes

Lanyard length: 1,750mm when shock absorber is intact - 2,450mm when shock absorber is fully deployed

Buckles: Interlocking, corrosion-resistant steel buckles with a minimum breaking force of 18kN

Hooks: Corrosion-resistant steel scaffolding hooks with 50mm gate opening



AVAILABLE WITH STANDING STEP, HYBRID LINE

**AGILIS HARNESS**  
HARN40000

**STANDARDS:**  
SANS 50261 | EN 261 + SANS 50250 | EN 250

**FEATURES:**  
• 4 attachment points: Chest & dorsal D-ring with work positioning D-rings  
• Adjustable leg, waist, shoulder & chest straps  
• Padded waist  
• Standing step

**MATERIALS:**  
Harness webbing: 45mm UV-resistant polyester webbing with a minimum breaking load of 2,5 tonnes

Padding: 5mm laminated foam to spread pressure over a larger area

Buckles: Interlocking, corrosion-resistant steel buckles with a minimum breaking force of 18kN



**ARC HARNESS**  
HARN70000

**STANDARDS:**  
SANS 50250 | EN 250 + SANS 50261 | EN 261  
ASDH P987-L2 (ATPV 40Cal/cm²)

**FEATURES:**  
• 4 Aluminium attachment points: Chest & dorsal D-ring with work positioning D-rings  
• Adjustable Aluminium quick-release buckles on the leg, waist and abdominal area with adjustable Aluminium buckles on the shoulder and back straps  
• Padding in the leg, waist, & shoulder areas  
• All attachment points, adjustments & padding are covered in full grain leather

**MATERIALS:**  
Harness webbing: Fire retardant & ARC flash rated, 45mm Para-aramid Meta-aramid blended webbing

Padding: 5mm laminated foam encased in full grain leather

Buckles: Aluminium corrosion-resistant quick-release buckles with a minimum breaking force of 18kN

D-Ring: Corrosion-resistant Aluminium D-rings with its breaking strength of 22kN



**GORDIAN HARNESS**  
HARN50000

**STANDARDS:**  
SANS 50261 | EN 261 + SANS 50250 | EN 250  
SANS 50262 | EN 262

**FEATURES:**  
• 5 attachment points: Front waist, chest & dorsal D-ring with work positioning D-rings & Gear loops  
• Adjustable leg, waist, shoulder & back straps  
• Padding in the leg & waist areas

**MATERIALS:**  
Harness webbing: 45mm UV-resistant polyester webbing with a minimum breaking load of 2,5 tonnes

Padding: 5mm laminated foam to spread pressure over a larger area

Buckles: Interlocking, corrosion-resistant steel buckles with a minimum breaking force of 18kN

Front Connector: Steel screw gate carabiner with a minimum breaking strength of 22kN



**SPARK HARNESS**  
HARN60000

**STANDARDS:**  
SANS 50261 | EN 261 + SANS 50250 | EN 250

**FEATURES:**  
• 4 attachment points: Chest & dorsal D-ring with work positioning D-rings  
• Adjustable leg, waist, shoulder & chest straps  
• Padded waist  
• Standing step

**MATERIALS:**  
Harness webbing: 45mm UV-resistant polyester webbing with a minimum breaking load of 2,5 tonnes

Padding: 5mm laminated foam to spread pressure over a larger area

Buckles: Interlocking, corrosion-resistant steel buckles with a minimum breaking force of 18kN



**LANYARDS**

**Double Leg Lanyard**  
LAN01220



**STANDARDS:**  
SANS 50254 | EN 254  
SANS 50255 | EN 255  
EN 262

**FEATURES:**  
Double leg with scarf hooks  
Single leg with trap hook  
Shock absorber

**Adjustable Double Leg Lanyard**  
LAN01420



**STANDARDS:**  
SANS 50254 | EN 254  
SANS 50255 | EN 255  
EN 262

**FEATURES:**  
Adjustable double leg with scarf hooks  
Single leg with screw gate carabiner  
Shock absorber

**Elasticated Double Leg Lanyard**  
LAN01620



**STANDARDS:**  
SANS 50254 | EN 254  
SANS 50255 | EN 255  
EN 262

**FEATURES:**  
Elasticated single leg with scarf hook  
Single leg with trap hook  
Shock absorber

**THE ORIGINAL TRAX IS BACK!**

We heard you! You've asked for it and now its back. Re-introducing the Original Trax Range by popular demand! The original and loved Trax collection is back. Designed with the rugged outdoors in mind, the Trax range boasts a wide-fitting, chunky and durable sole unit that can handle the toughest terrains while providing the all-day superior comfort that earned Trax its following.

**MUNICH 20002**



Size	Colour	Accreditations
5-13	Black	SANS/ISO 20345 NRC5/9002/287766/0162

**TOE CAP:** Steel - Extra-wide Fitting  
**SOLE:** Dual Density PU/PU (heat resistant up to 95°C)  
**MIDSOLE:** SMS available (207002)



**BREMEN 20001**



Size	Colour	Accreditations
5-13	Black	SANS/ISO 20345 NRC5/9002/287766/0162

**TOE CAP:** Steel - Extra-wide Fitting  
**SOLE:** Dual Density PU/PU (heat resistant up to 95°C)  
**MIDSOLE:** SMS available (207001)



**HIKER 20013**



Size	Colour	Accreditations
5-13	Black & Walnut (HTO)	SANS/ISO 20345 NRC5/9002/287766/0146

**TOE CAP:** Steel - Extra-wide Fitting  
**SOLE:** Dual Density PU/PU (heat resistant up to 95°C)  
**MIDSOLE:** Shank reinforcement for arch support



**EXTREMEWEAR**

PU/RUBBER

**FIREWALK B-42003**

Anti-shock Safety Boot



ELECTRICAL RESISTANCE TO 20KV FOR 60 SECONDS (EN ISO 20345)  
NON-CONDUCTIVE



Sizes: 4-13  
Colour: Black

- Dual Density PU/Rubber sole
- Steel toe cap
- Heat-resistant up to 300°C
- Full Grain Leather upper
- Non-conductive

SANS / ISO 20345 NRCS/9002/287766/0134  
APT MIDSOLE AVAILABLE (H4602 - NRCS/9002/287766/0454)

**EXTREMEWEAR**

PU/RUBBER

**WELDERS B-42004**

Welders Safety Boot



NON-CONDUCTIVE  
ANTI-STATIC



Sizes: 4-13  
Colour: Black

- Dual Density PU/Rubber sole
- Steel toe cap
- Heat-resistant up to 300°C
- Full Grain Leather upper
- Spot covering with stainless steel buckles
- Non-conductive

SANS / ISO 20345 NRCS/9002/287766/0135

**HEAVYWEAR**

CORE RANGE

**RADICAL B-60001**

Durable Safety Shoe



ANTI-STATIC



Sizes: 4-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Genuine Split Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0165

**HEAVYWEAR**

CORE RANGE

**HAVERICK B-60002**

Durable Safety Boot



ANTI-STATIC



Sizes: 4-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Genuine Split Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0171  
SMS AVAILABLE (S0702 - NRCS/9002/287766/0290)

**EXTREMEWEAR**

PU/RUBBER

**ROCNA B-43601**

Extreme Slip Safety Shoe



ELECTRICAL RESISTANCE TO 20KV FOR 60 SECONDS (EN ISO 20345)  
NON-CONDUCTIVE  
EN SLIP RESISTANCE RATING



Sizes: 4-13  
Colour: Black

- Dual Density PU/Vibram Rubber sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 300°C
- Full Grain Wavy Leather upper
- Anti-penetration in-sock
- Non-conductive
- Approved by the Podiatry Association of South Africa

SANS / ISO 20345 NRCS/9002/287766/0437

**EXTREMEWEAR**

PU/RUBBER

**DROGUE B-43602**

Extreme Slip Safety Boot



ELECTRICAL RESISTANCE TO 20KV FOR 60 SECONDS (EN ISO 20345)  
NON-CONDUCTIVE  
EN SLIP RESISTANCE RATING



Sizes: 4-13  
Colour: Black

- Dual Density PU/Vibram Rubber sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 300°C
- Full Grain Wavy Leather upper
- Anti-penetration in-sock
- Non-conductive
- Approved by the Podiatry Association of South Africa

SANS / ISO 20345 NRCS/9002/287766/0437

**HEAVYWEAR**

CORE RANGE

**NEOGRIP B-90005**

Durable Safety Shoe



ANTI-STATIC



Sizes: 5-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0117  
SMS AVAILABLE (90705 - NRCS/9002/287766/0434)

**HEAVYWEAR**

CORE RANGE

**NEOFLEX B-90004**

Durable Safety Boot



ANTI-STATIC



Sizes: 3-15  
Colour: Black & Tan

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0055  
SMS AVAILABLE (90704 - NRCS/9002/287766/0430)

**EXTREMEWEAR**

PU/RUBBER

**NEBULA B-43603**

Extreme Slip Safety Boot



ELECTRICAL RESISTANCE TO 20KV FOR 60 SECONDS (EN ISO 20345)  
NON-CONDUCTIVE  
EN SLIP RESISTANCE RATING



Sizes: 4-13  
Colour: Brown

- Dual Density PU/Vibram Rubber sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 300°C
- Full Grain Leather upper
- Anti-penetration in-sock
- Non-conductive
- Approved by the Podiatry Association of South Africa

SANS / ISO 20345 NRCS/9002/287766/0487

**EXTREMEWEAR**

RUBBER/RUBBER

**BASALT B-7142**

Safety Boot



EN SLIP RESISTANCE RATING  
ANTI-STATIC  
ANTI-STATIC



Sizes: 4-14  
Colour: Black

- Dual Compound Rubber/Rubber sole
- Steel toe cap
- Heat-resistant up to 300°C
- Full Grain Leather upper
- Elastic side gussets for ease of entering and exiting the boot
- Anti-static

SANS / ISO 20345 NRCS/9002/287766/0448

**HEAVYWEAR**

CORE RANGE

**TRAINER B-60012**

Durable Safety Shoe



ANTI-STATIC



Sizes: 4-12  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Full Grain Leather upper
- Anti-static

SANS / ISO 20345 NRCS/9002/287766/0069

**HEAVYWEAR**

CORE RANGE

**CHELSEA B-90006**

Durable Safety Boot



ANTI-STATIC



Sizes: 3-13  
Colour: Black & Brown

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 90°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0170



## HEAVYWEAR

## CORE RANGE

## HAMBURG B-90008

Durable Safety Shoe



Sizes: 4-12  
Colour: Grey

- Dual Density PU/PU sole
- Steel toe cap
- Heat-resistant up to 95°C
- Guede Leather upper
- Anti-static

SANS / ISO 20345 NRCS/9002/287766/0116

## LIGHTWEAR

## UTILITY RANGE

## MULTI B-71441

Utility Safety Shoe



Sizes: 5-13  
Colour: Black

- Single Density PU sole
- Steel toe cap
- Heat-resistant up to 95°C
- Genuine Split Leather upper

SANS / ISO 20345 NRCS/9002/287766/0120

## HEAVYWEAR

## AKTIV RANGE

## ATLANTIS B-30006

Metal-free Safety Shoe with Comfort Engineering



Sizes: 5-12  
Colour: Black

- Dual Density PU/PU sole
- Composite toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static
- Approved by the Podiatry Association of South Africa

SANS / ISO 20345 NRCS/9002/287766/0428

## LIGHTWEAR

## EXECUTIVE RANGE

## JARMAN B-70003

Executive Safety Shoe



Sizes: 5-12  
Colour: Black

- Single Density PU sole
- Steel toe cap
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 SANS / ISO NRCS/9002/287766/0409

## LIGHTWEAR

## UTILITY RANGE

## ADAPT B-71442

Utility Safety Boot



Sizes: 5-13  
Colour: Black

- Single Density PU sole
- Steel toe cap
- Heat-resistant up to 95°C
- Genuine Split Leather upper

SANS / ISO 20345 NRCS/9002/287766/0119

## HEAVYWEAR

## AKTIV RANGE

## COLUMBIA B-30005

Metal-free Safety Boot with Comfort Engineering



Sizes: 5-12  
Colour: Black

- Dual Density PU/PU sole
- Composite toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static
- Approved by the Podiatry Association of South Africa

SANS / ISO 20345 NRCS/9002/287766/0288

## HEAVYWEAR

## TRAX RANGE

## TAHOE Z1021

Advanced Comfort Safety Shoe



Sizes: 5-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0432

## HEAVYWEAR

## TRAX RANGE

## BREMEN 2.0 B-21001

Advanced Comfort Safety Shoe



Sizes: 5-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0446  
SMS AVAILABLE (21701 - NRCS/9002/287766/0449)

## HEAVYWEAR

## TRAX RANGE

## HIKER 2.0 Z1013

Advanced Comfort Safety Boot



Sizes: 5-13  
Colour: Black and Brown

- Dual Density PU/PU sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0390

## HEAVYWEAR

## TRAX RANGE

## MUNICH 2.0 B-21002

Advanced Comfort Safety Boot



Sizes: 5-13  
Colour: Black

- Dual Density PU/PU sole
- Steel toe cap - extra-wide fitting
- Heat-resistant up to 95°C
- Full Grain Leather upper
- Anti-static

EN / ISO 20345 NRCS/9002/287766/0447  
SMS AVAILABLE (21702 - NRCS/9002/287766/0450)

## ACCESSORIES



## BOVA SOX FOR MEN

- Anti-bacterial
- Anti-static
- Available to purchase separately
- Included with footwear where the FREE BOVA SOX logo is shown

ACC13677



## BOVA FREEZER SOX FOR MEN

- Anti-bacterial
- Anti-static
- Available to purchase separately

ACC13680



## SMELTERS SOX FOR MEN

- Wool sock
- Anti-bacterial
- Flame-retardant
- Moisture-wicking
- Recommended for high heat conditions

ACC13672



## FOOTOLOGY SOX UNISEX ANKLET

- Anti-bacterial
- Anti-static
- Sizing: 4-8, 9-12

ACC13667